

a forefoot portion, including a plurality of elongated elements that extend from the lateral side to the medial side, and from the midfoot portion into substantially an entire length of the forefoot portion, the plurality of elongated elements defining at least one space therebetween extending from a forwardmost extent of the forefoot portion and terminating in the midfoot portion; and

a rearfoot portion, including at least one elongated element that extends from the midfoot portion into substantially an entire length of a heel portion of the chassis.

C2  
11. (Amended) The chassis of claim 10, wherein the chevron opens to one of the medial side or the lateral side of the chassis.

C3  
20. (Three Times Amended) A single piece generally planar polymeric chassis for installation in an article of footwear, the chassis comprising a plurality of elongated elements that extend from a lateral side to a medial side of the chassis and extend substantially along an entire length from a heel portion of the chassis to a toe portion of the chassis, each elongated element comprising:

a midfoot portion;

a forefoot portion; and

a rearfoot portion;

wherein the plurality of elongated elements define at least one space therebetween extending from a forwardmost extent of the forefoot portion of the plurality of elongated elements and terminating in the midfoot portion.

C4  
26. (Three Times Amended) An article of footwear including a sole with at least one cleat, the sole comprising a polymeric chassis, wherein a forefoot portion of the chassis has a lateral side and a medial side, the lateral and medial sides being proximate to corresponding lateral and medial sides of the article of footwear, the

chassis extending substantially along an entire length of (i) a heel portion of the article of footwear, and (ii) a toe portion of the article of footwear.

(N. Sub p2) 39. (Amended) A polymeric chassis for installation in an article of footwear, the chassis comprising at least three elongated elements that extend from a lateral side to a medial side of the chassis and extend substantially along an entire length of the chassis from a heel portion of the chassis to a toe portion of the chassis, each elongated element comprising:

a midfoot portion;

a forefoot portion; and

a rearfoot portion.